

Solvable Iron & Rust Remover

Version number: 1.0

Date of compilation: 2026-03-17

1 Identification

1.1 Product identifier

Trade name	Solvable Iron & Rust Remover
SDS ID	BB 07503
Product Code	53-20070

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Vehicle cleaner Professional use Industrial use
--------------------------	---

1.3 Details of the supplier of the safety data sheet

Recochem Inc.
8725 Holgate Crescent
Milton Ontario L9T 5G7
Canada
Telephone: 1-800-361-6030

1.4 Emergency telephone number

Emergency information service	CANUTEC 1-613-996-6666, 24 hours. POISON CONTROL / ANTIPOISON (24 heures/hours): Alberta 1-800-332-1414 British Columbia 1-800-567-8911 Manitoba 1-855-776-4766 New Brunswick 911 Newfoundland and Labrador 1-866-727-1110 Northwest Territories 1-800-332-1414 Nova Scotia and Prince Edward Island 1-800-565-8161, 1-800-332-1414 or 911. Nunavut 1-800-268-9017 Ontario 1-800-268-9017 Quebec 1-800-463-5060 Saskatchewan 1-866-454-1212 Yukon Territory 867-393-8700 United States 1-800-222-1222 24 hr emergency information
-------------------------------	--

2 Hazard identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Cat-egory	Hazard class and category	Hazard statement
3.4S	skin sensitization	1	Skin Sens. 1	H317

For full text of abbreviations: see SECTION 16.

2.2 Label elements

Labeling

- Signal word warning

- Pictograms

GHS07



- Hazard statements

H317 May cause an allergic skin reaction.

Solvable Iron & Rust Remover

Version number: 1.0

Date of compilation: 2026-03-17

- Precautionary statements

- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
- P302+P352 IF ON SKIN: Wash with plenty of water.
- P321 Specific treatment (see on this label).
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P501 Dispose of contents/container to industrial combustion plant.

- Hazardous ingredients for labelling (2-hydroxyethyl)ammonium mercaptoacetate

2.3 Other hazards

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of $\geq 0.1\%$.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0.1\%$.

3 Composition/ Information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Hazardous ingredients acc. to GHS				
Name of substance	Identifier	Wt%	Classification acc. to GHS	Notes
(2-hydroxyethyl)ammonium mercaptoacetate	CAS No 126-97-6	5 – < 10	Acute Tox. 4 / H302 Skin Sens. 1B / H317	
2-(2-butoxyethoxy)ethanol	CAS No 112-34-5	1 – < 5	Eye Irrit. 2 / H319	
beta-Pinene	CAS No 127-91-3	< 0.1	Flam. Liq. 3 / H226 Skin Irrit. 2 / H315 Skin Sens. 1 / H317 Asp. Tox. 1 / H304	
Tangerine oil	CAS No 8016-85-1	< 0.1	Flam. Liq. 3 / H226 Skin Irrit. 2 / H315 Skin Sens. 1 / H317 Asp. Tox. 1 / H304	

Remarks

For full text of abbreviations: see SECTION 16. Exact percentage of ingredients is withheld as a trade secret.
This table, if present, includes all GHS classified ingredients present above their cut-off limits, even if the finished product is not classified as hazardous by GHS.

4 First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Solvable Iron & Rust Remover

Version number: 1.0

Date of compilation: 2026-03-17

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

5 Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, Alcohol resistant foam, BC-powder, Carbon dioxide (CO₂)

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Nitrogen oxides (NO_x), Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

7 Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Solvable Iron & Rust Remover

Version number: 1.0

Date of compilation: 2026-03-17

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Control of the effects

Protect against external exposure, such as
frost

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

8 Exposure controls/ Personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
CA	diethylene glycol monobutyl ether	112-34-5	OEL (ON-MoL)	10						iv	MoL
CA	6,6-dimethyl-2-methylene-bicyclo(3.1.1)heptane	127-91-3	OEL (ON-MoL)	20							MoL
CA	β-pinene	127-91-3	OEL (AB)	20	111						OHS Code
CA	β-pinene	127-91-3	OEL (BC)	20							"BC Regulation"
CA	β-pinene	127-91-3	PEV/VEA	20	112						Regulation OHS

Notation

Ceiling-C	ceiling value is a limit value above which exposure should not occur
iv	inhalable fraction and vapor
STEL	short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
TWA	time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Relevant DNELs of components						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
(2-hydroxyethyl)ammonium mercaptoacetate	126-97-6	DNEL	1.41 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
(2-hydroxyethyl)am-	126-97-6	DNEL	2.06	human, dermal	worker (industry)	chronic - systemic

Solvable Iron & Rust Remover

Version number: 1.0

Date of compilation: 2026-03-17

Relevant DNELs of components						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
monium mercaptoacetate			mg/kg bw/day			effects
2-(2-butoxyethoxy)ethanol	112-34-5	DNEL	67.5 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
2-(2-butoxyethoxy)ethanol	112-34-5	DNEL	83 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
2-(2-butoxyethoxy)ethanol	112-34-5	DNEL	67.5 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
2-(2-butoxyethoxy)ethanol	112-34-5	DNEL	101.2 mg/m ³	human, inhalatory	worker (industry)	acute - local effects

Relevant PNECs of components						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
(2-hydroxyethyl)ammonium mercaptoacetate	126-97-6	PNEC	38 µg/l	aquatic organisms	freshwater	short-term (single instance)
(2-hydroxyethyl)ammonium mercaptoacetate	126-97-6	PNEC	3.8 µg/l	aquatic organisms	marine water	short-term (single instance)
(2-hydroxyethyl)ammonium mercaptoacetate	126-97-6	PNEC	3.2 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	200 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	4 mg/kg	benthic organisms	sediments	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	56 mg/kg	(top) predators	water	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	3.9 mg/l	aquatic organisms	water	intermittent release
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	0.4 mg/kg	pelagic organisms	sediments	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	200 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	1.1 mg/l	aquatic organisms	freshwater	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	0.11 mg/l	aquatic organisms	marine water	short-term (single instance)

Solvable Iron & Rust Remover

Version number: 1.0

Date of compilation: 2026-03-17

Relevant PNECs of components						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	4.4 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	0.44 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	0.32 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Color	orange
Odor	citrus - slightly sulfurous
Melting point/freezing point	not determined
Boiling point or initial boiling point and boiling range	100 °C
Flammability	this material is combustible, but will not ignite readily
Lower and upper explosion limit	not determined
Flash point	>100 °C at 101.3 kPa
Auto-ignition temperature	210 °C (auto-ignition temperature (liquids and gases))

Solvable Iron & Rust Remover

Version number: 1.0

Date of compilation: 2026-03-17

Decomposition temperature	not relevant
pH (value)	7 – 8 (25 °C)
Kinematic viscosity	not determined

Solubility(ies)

Water solubility	miscible in any proportion
------------------	----------------------------

Partition coefficient

Partition coefficient n-octanol/water (log value)	this information is not available
---	-----------------------------------

Vapor pressure	31.69 hPa at 25 °C
----------------	--------------------

Density and/or relative density

Density	1.1 g/cm ³ at 25 °C
Relative vapour density	information on this property is not available

Particle characteristics	not relevant (liquid)
--------------------------	-----------------------

9.2 Other information

Information with regard to physical hazard classes	hazard classes acc. to GHS (physical hazards): not relevant
--	--

Other safety characteristics

Miscibility	Completely miscible with water.
Temperature class (USA, acc. to NEC 500)	T3 (maximum permissible surface temperature on the equipment: 200°C)

10 Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

Mixture with acids will generate poisonous hydrogen sulphide gas.

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

Acids, Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are

Solvable Iron & Rust Remover

Version number: 1.0

Date of compilation: 2026-03-17

not known. Hazardous combustion products: see section 5.

11 Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4: May be harmful if swallowed.

Acute toxicity estimate (ATE) of components			
Name of substance	CAS No	Exposure route	ATE
(2-hydroxyethyl)ammonium mercaptoacetate	126-97-6	oral	318 mg/kg
(2-hydroxyethyl)ammonium mercaptoacetate	126-97-6	dermal	>2,000 mg/kg
2-(2-butoxyethoxy)ethanol	112-34-5	oral	2,410 mg/kg
2-(2-butoxyethoxy)ethanol	112-34-5	dermal	2,764 mg/kg

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

May cause an allergic skin reaction.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

12 Ecological information

12.1 Toxicity

Toxic to aquatic life with long lasting effects.

Solvable Iron & Rust Remover

Version number: 1.0

Date of compilation: 2026-03-17

Aquatic toxicity (acute) of components					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
(2-hydroxyethyl)ammonium mercaptoacetate	126-97-6	LC50	>100 mg/l	fish	96 h
(2-hydroxyethyl)ammonium mercaptoacetate	126-97-6	EC50	>100 mg/l	aquatic invertebrates	48 h
(2-hydroxyethyl)ammonium mercaptoacetate	126-97-6	ErC50	65 mg/l	algae	72 h
2-(2-butoxyethoxy)ethanol	112-34-5	LC50	1,300 mg/l	fish	96 h
2-(2-butoxyethoxy)ethanol	112-34-5	EC50	>100 mg/l	aquatic invertebrates	48 h
2-(2-butoxyethoxy)ethanol	112-34-5	ErC50	>100 mg/l	algae	96 h

Aquatic toxicity (chronic) of components					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
(2-hydroxyethyl)ammonium mercaptoacetate	126-97-6	EC50	>1,000 mg/l	microorganisms	3 h

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of $\geq 0.1\%$.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0.1\%$.

12.7 Other adverse effects

Data are not available.

13 Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

Solvable Iron & Rust Remover

Version number: 1.0

Date of compilation: 2026-03-17

14 Transport information

14.1 UN number

UN RTDG	UN 3082
IMDG-Code	UN 3082
ICAO-TI	UN 3082

14.2 UN proper shipping name

UN RTDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
IMDG-Code	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
ICAO-TI	Environmentally hazardous substance, liquid, n.o.s.

14.2.6 Technical name (hazardous ingredients)

Disodium 4,5-dihydroxybenzene-1,3-disulphonate, grapefruit oil terpenes

14.3 Transport hazard class(es)

UN RTDG	9
IMDG-Code	9
ICAO-TI	9

14.4 Packing group

UN RTDG	III
IMDG-Code	III
ICAO-TI	III

14.5 Environmental hazards

	hazardous to the aquatic environment
Environmentally hazardous substance (aquatic environment)	Disodium 4,5-dihydroxybenzene-1,3-disulphonate, grapefruit oil terpenes

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport information - National regulations - Additional information (UN RTDG)

UN number	3082
Class	9
Environmental hazards	yes (hazardous to the aquatic environment)
Packing group	III
Danger label(s)	9, fish and tree



Special provisions (SP)	274, 331, 335, 375 (UN RTDG)
-------------------------	------------------------------

Solvable Iron & Rust Remover

Version number: 1.0

Date of compilation: 2026-03-17

Excepted quantities (EQ)	E1 (UN RTDG)
Limited quantities (LQ)	5 L (UN RTDG)
International Maritime Dangerous Goods Code (IMDG)	
Marine pollutant	yes (hazardous to the aquatic environment) (Disodium 4,5-di-hydroxybenzene-1,3-disulphonate)
Danger label(s)	9, fish and tree
	
Special provisions (SP)	274, 335, 375, 969
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
EmS	F-A, S-F
Stowage category	A
International Civil Aviation Organization (ICAO-IATA/DGR)	
Environmental hazards	yes (hazardous to the aquatic environment)
Danger label(s)	9, fish and tree
	
Special provisions (SP)	A97, A158, A197, A215
Excepted quantities (EQ)	E1
Limited quantities (LQ)	30 kg

15 Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA) all ingredients are listed

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

Clean Air Act

none of the ingredients are listed

VOC content

- Regulated Volatile Organic Compounds (VOC-EPA)	0.2259 %
- Regulated Volatile Organic Compounds (VOC-Cal ARB)	0.2265 %

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Solvable Iron & Rust Remover

Version number: 1.0

Date of compilation: 2026-03-17

Category	Rating	Description
Chronic	/	none
Health	2	temporary or minor injury may occur
Flammability	1	material that must be preheated before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

Chronic: chronic hazard
 Flammability: flammability hazards
 Health: health hazard
 Personal protection: personal protective equipment (PPE) for normal use
 Physical hazard: reactivity

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	1	material that must be preheated before ignition can occur
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National regulations (Canada)

Domestic Substances List (DSL)

All ingredients are listed.

National inventories

Country	Inventory	Status
CA	DSL	all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
US	TSCA	all ingredients are listed (ACTIVE)
AU	AIIC	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	not all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	not all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed

Solvable Iron & Rust Remover

Version number: 1.0

Date of compilation: 2026-03-17

Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

Additional information

The contained substances are listed in the following national inventories:

AIIC (Australia)
 DSL/NDSL (Canada)
 IECSC (China)
 PICCS (Philippines)
 TCSI (Taiwan)
 TSCA (United States)

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

16 Other information

Indication of changes (revised safety data sheet)

Alignment to regulation: Globally Harmonized System of Classification and Labelling of Chemicals ("Purple book").
 Restructuring: section 9, section 14

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
"BC Regulation"	OHS Regulation: Section 5.48 (British Columbia)
Acute Tox.	Acute toxicity
AIIC	Australian Inventory of Industrial Chemicals
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
Cal ARB	California Air Resources Board
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
ED	Endocrine disruptor
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule

Solvable Iron & Rust Remover

Version number: 1.0

Date of compilation: 2026-03-17

Abbr.	Descriptions of used abbreviations
EPA	Environmental Protection Agency. An agency of the federal government of the United States charged with protecting human health and the environment
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
MoL	Ministry of Labor: Current Occupational Exposure Limits for Ontario Workplaces Required under Regulation 833
NLP	No-Longer Polymer
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OHS Code	Occupational Health and Safety Code: Occupational exposure limits for chemical substances (Alberta)
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
Regulation OHS	Regulation respecting occupational health and safety: Permissible exposure values for airborne contaminants (Quebec)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
Skin Sens.	Skin sensitization
STEL	Short-term exposure limit
TWA	Time-weighted average
UN RTDG	UN Recommendations on the Transport of Dangerous Good
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

Hazardous Products Regulations (HPR)
 SOR/2022-272: Regulations Amending the Hazardous Products Regulations (GHS, Seventh Revised Edition)
 UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG).
 Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.
 Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Solvable Iron & Rust Remover

Version number: 1.0

Date of compilation: 2026-03-17

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.